



## MADE IN GERMANY

Wassermann is a medium-sized, owner-operated company with head office in Hamburg. We design and produce high-quality technical devices in Germany. Our main users are dental laboratories, dental clinics and various industrial areas worldwide.

### Why a Wassermann product?

Wassermann products are manufactured from high-quality materials and the proportion of plastics used is intentionally kept as low as possible. Our devices are known for their suitability for daily use, functionality and longevity. As a result, the users place high levels of trust in the Wassermann brand. We feel it is our duty to support our customers on a daily basis when it comes to safety, service and productivity. Technological perfection, optimum quality and especially sustainability are the benchmarks we set. Thanks to the combination of these values, the family-owned company, since its establishment in 1927, has gained worldwide recognition as a manufacturer of high-quality products.



Further information are available on our website at [www.wassermann.hamburg](http://www.wassermann.hamburg)



/WassermannDentalmaschinen

Your Dental Dealer \_\_\_\_\_

## Gobi Classic



## Fine Blasting Unit



Wassermann Dental-Maschinen GmbH  
Rudorffweg 15-17 · 21031 Hamburg · Germany  
Phone: +49 (0)40 730 926-20/ -24 · Fax: +49 (0)40 730 37 24  
export@wassermann-dental.com · www.wassermann.hamburg  
www.facebook.com/WassermannDentalmaschinen

# Fine Blasting Unit **Gobi Classic**

The **Gobi Classic** is a precision fine blasting unit with two tanks. It is the perfect unit for sand-blasting, roughening or polishing using all common blasting materials and grain sizes. The unit works precise and has low maintenance. The entire system is continuously under pressure and is therefore always ready for use. Even when switching on the unit again, you can use the quick-start- and quick-stop function to begin blasting immediately. This is possible due to the crushing valve at the conducting hose.

We recommend the use of Wassermann blasting materials and our low-pressure suction units **SG-10**, **SG-1/1** and **SG-1/2 D**.

Precise working pressure of 0.8–6 bar with pressure gauge control

Permanent pressure system: Prevents contamination and moisture of blasting material

Easy choice of the desired blasting material by using the selection switch for colour circuit settings

With plug socket, e.g. for a suction unit

Simple cleaning due to stay-clean surfaces: High quality stainless steel and robust plastic powder coating

Rapid ventilation of the high quality blasting material containers made of metal for rapid re-filling and changing of blasting material

Optimum workspace illumination, protected LED lamp

Air inlet membrane: If needed cut in the rubber vertically and horizontally to achieve an optimum exhaust air stream into the vent of the connected suction unit



## Major Features

- Genuine quick start/stop function, foot-controlled
- Comfortably to handle with ergonomically shaped handpieces
- Cost savings thanks to noticeable low consumption of blasting material
- High hygiene standard because of changeable sleeves
- Special particularly durable hoses
- Convenient colour coding system
- Specially coated safety screen for ideal visibility
- Designed for long durability
- **Included in delivery:**  
**Gobi Classic** incl. 2 fine blasting nozzles: 0.8 (blue), 1.2 (red)  
 Compressed air hose, 2 m  
 592012 Supply line 3 core with angle plug  
 (Delivered only on request: 592011 Supply line 3 core US 13 A)

Accessories	Item no.
Extractor nozzle Ø 40 mm exterior	143385
Extractor nozzle Ø 50 mm exterior	190286
Compressed air hose per meter	320026
Spare fine blasting nozzle 0.6 mm	190550
Spare fine blasting nozzle 0.8 mm	190551
Spare fine blasting nozzle 1.2 mm	190552

Gobi Classic	Item no. 190881
Voltage	100–240 V / 50/60 Hz
Power consumption	0.2 A
Plug socket power consumption	max. 8 A
Output	50 W
W x H x D	444 x 372 x 520 mm
Weight	14 kg
Sound level	≤ 70 dB (A)
Tank capacity	420 cm <sup>3</sup>
Compressed air connection	3–6 bar
Working pressure	0.8–6 bar
Extractor nozzle	Ø 75 mm exterior